PRODUCT
DATA SHEET

VERSION 1





Fully Automatic

Tripod Turnstile

PRODUCT DATA SHEET | UKT-12 Internal Tripod

The UKT-12 Tripod model is a slimline unit which features a centrally mounted LED indicator with corresponding colours at each end. It has options for either CCTV cameras or facial readers with one or two mounting points.

This model can be used internally as standard or also designed for external use IP65. It has an active passage width of 550mm making this product suitable for a wide range of environments where single or multiple lane access is required.

The unit has an emergency release mechanism that allows the rotas to drop away for unrestricted access; this can also be linked to a fire alarm system.

KEY PRODUCT FEATURES:

- Low Power Consumption
- Two way or one way working
- LED indication panels
- IP65 rated for internal/external use
- Can be integrated with any fire and access control systems
- Sound and light prompts and adjustable volume
- Fail safe on power failure (see website for details)

TECHNICAL SPECIFICATIONS:

DESCRIPTION	VALUE	UNIT OF MEASUREMENT
Dimensions Straight Arm	1600mm x 980mm x 150mm	HxWxD
Weight	75	KG
Passage Width	575 (Including 25mm pinch point)	mm
Throughput	20 ~ 40	Persons / min
Electrical Input	230	V

ADDITIONAL OPTIONS:

This unit has additional access control mounting points if required.

Single Lane	Twin Lane	Triple Lane	IP65

DRAWINGS:

